

New Holland T7000 Series Tractor Specifications



T7030 T7040 T7050 T7060

MODEL	T7030	T7040	T7050	T7060
ENGINE				
Gross engine horsepower, hp (kW)	165 (123)	180 (134.2)	195 (145.4)	210 (156.6)
Rated PTO, hp (kW)	135 (100.7)	150 (111.9)	165 (123)	180 (134.2)
Rated speed, rpm		2200.		
Power boost @ 1900 rpm (PTO & transport modes), hp (kW)	35 (26)	35 (26)	35 (26)	25 (19)
Cylinders/displacement, cu. in. (L)		6 / 411 (6.75)		
Number of valves		24		
Aspiration		Turbocharged/intercooled		
ELECTRICAL				
Standard alternator, amp/volt		150/12		
Battery capacity (1 battery), CCA		1300.		
TRANSMISSION				
18x6 Power Command™ full powershift		Standard		
Creeper with additional 10F/6R		Optional		
19x6 Power Command, 31 mph (50 kph) max speed		Optional		
19x6 Power Command economy transmission		Optional		
PTO – standard (reversible shaft), in. (mm)		540/1000 rpm, 1-3/8 (35)		
PTO – optional, in. (mm)		1000 rpm, 1-3/4 (45)		
AXLES				
Standard rear diameter, in. (mm)		4-1/8 (105)		
Rear axle length – standard, in. (mm)		112 (2485)		
Rear axle length – optional, in. (mm)		98 (2489) or 119 (3023)		
Standard FWD axle w/ TerraLock™		Standard		
SuperSteer™ FWD axle w/ TerraLock		Optional		
TerraGlide™ active suspended axle w/ TerraLock		Optional		
FWD tread adjustability, in. (mm)		60-88 (1524-2235)		
Wheelbase (MFD), in. (mm)		113.6 (2884)		
HYDRAULICS				
Hydraulic type		Closed center load sensing		
Rear remote options		3 or 4 mechanical, 3 to 5 electrohydraulic		
Main/implement pump flow – std./opt., gpm (L/min)		32.0 (120) / 39.6 (150)		
Steering and services pump flow, gpm (L/min)		17 (66)		
Total tractor hydraulic flow – std./opt., gpm (L/min)		49.0 (186) / 56.6 (216)		
3-point hitch category		Cat. II / IIIN		
3-point hitch lift capacity, lb. (kg)	12,787 (5800)			15,873 (7200)
CAPACITIES				
Fuel tank, U.S. gal. (L)		116 (440)		
Engine oil, U.S. qt. (L)		16 (15)		
Hydraulic fluid, U.S. gal. (L)		26.5 (100)		
HORIZON™ CAB W/ HI-VISIBILITY PANEL				
Glass area including hi-visibility panel, sq. ft. (m²)		63 (5.85)		
Sound level, dBA		70		
SHIPPING WEIGHT				
Std MFD w/ 18.4R42 & front weight bracket, lb. (kg)		15,708 (7125)		
Height to top of cab, 18.4R42, in. (mm)		119.7 (3040)		
Height to top of exhaust, 18.4R42, in. (mm)		122.6 (3114)		

Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.