



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PS-615-HG-OEM

Power Strip with Hospital-Grade Plug & Receptacles (TUV tested to UL)



Highlights

- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 6 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- Two 15-amp resettable circuit breakers
- Lifetime product warranty

Description

Tripp Lite's PS-615-HG-OEM Power Strip is designed to be installed on any mobile cart, IV pole, etc. It is TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted. Features 6 output receptacles, 15-ft. AC power cord and two built-in resettable circuit breakers that control power to all outlets and protect against overloads. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

Applications

- Mobile carts, IV poles and other UL 1363A usages.

Package Includes

- PS-615-HG-OEM
- User manual with warranty information

Features

- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 6 x NEMA 5-15R-HG hospital-grade output receptacles
- 15-ft. AC cord with integrated, molded NEMA 5-15P-HG hospital-grade plug
- Rugged all-metal housing withstands years of use without breakage
- 15A electrical capacity with two built-in resettable circuit breakers
- 120V, 50/60Hz
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Outlet quantity / type	6 x NEMA 5-15R-HG Hospital-Grade
Outlet orientation	Single row of 6
Overload protection	2 x 15amp breaker (1 line, 1 neutral)
INPUT	
Input connection type	NEMA 5-15P-HG Hospital-Grade
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	15
Input cord length (m)	4.572
Recommended Electrical Service	15A, 120V
LEDS ALARMS & SWITCHES	
Switches	No power switch
PHYSICAL	
Shipping weight (lbs)	3.55
Shipping Dimensions (HWD/in)	15 x 6 x 3.55
Unit weight (lbs)	2.25
Unit Dimensions (HWD/in)	13.75 x 2.5 x 1.5
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
Receptacle Color	White
AC line cord color	White
CERTIFICATIONS	
Additional International Approvals	TUV tested to UL 1363A
WARRANTY	
Product Warranty Period	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3719.