


RoHS Compliant

UC-235 / UC-246

UNIVERSAL 1 PORT RS232

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Description

Universal PCI providing one RS232 serial port. Up to 115,200 data transfer rates and the 128 byte deep transmit and 128 byte receive FIFOs, coupled with 1Mbit/s line drivers deliver uncompromising performance on your laptop/PC.

Universal PCI is fully compatible with both 3.3Volt and 5Volt PCI slots.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Features

- 1 Port RS232
- Universal PCI
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 & Windows 2000
- Windows Vista 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit Editions
- Windows Server 2003 32 bit & 64 bit Editions



As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.

Options



UC-235:
UNIVERSAL 1 PORT
RS232 LOW PROFILE



UC-246
UNIVERSAL 1 PORT
RS232




ORDER

Description

UNIVERSAL 1 PORT RS232 LOW PROFILE
UNIVERSAL 1 PORT RS232

Code

UC-235
UC-246



UNIVERSAL 1 PORT RS232

UC-235 / UC-246: Full Specification

<p>Port</p>	<p>Ports</p> <p>Connector</p> <p>FIFO size</p> <p>Operating Distance</p> <p>Cable</p>	<p>1 Port RS232</p> <p>DB9 connector (9 Pin Male)</p> <p>128 Tx, 128 Rx</p> <p>EIA - RS232 Standard</p>
<p>Port Settings</p> <p>115,200 ▶▶▶▶ baud</p>	<p>Baud Rate</p> <p>Data Bits</p> <p>Parity</p> <p>Stop Bits</p> <p>Flow Control</p> <p>Tx/Rx Modes</p>	<p>Up to 115,200</p> <p>5,6,7 or 8</p> <p>Odd, Even, None, Mark or Space</p> <p>1, 1.5 or 2</p> <p>RTS/CTS DSR/DTR XON/XOFF</p> <p>Point to Point</p>
<p>Interface</p> <p>PCI</p>	<p>OS Compatibility</p> <p>BUS</p>	<p>Windows Vista 32 bit and 64 bit Editions Windows Server 2008 32 bit and 64 bit Editions Windows Server 2003 32 bit and 64 bit Editions Windows XP 32 bit and 64 bit Editions Windows 2000</p> <p>PCI 3.0</p>
<p>Approvals</p>	<p>Other Approvals</p> <p>Microsoft Approvals</p>	<p>IEEC CB Scheme METL VCCI WEEE FCC compliant</p> <p>Microsoft Certified Gold Partner Windows XP 32 bit & 64 bit Windows Server 2008 32 bit and 64 bit</p>
<p>General</p>	<p>PCB Layers</p> <p>Power Consumption</p> <p>Weight</p> <p>Size</p>	<p>4</p> <p>190mA @ 5V, 12mA @ 12V</p> <p>0.097Kg</p> <p>64 x 122 mm</p>
<p>Box Content</p>	<p>Packaging</p> <p>Card</p>	<p>Installation CD including manual, Microsoft signed drivers & utilities</p> <p>UNIVERSAL 1 PORT RS232</p>
<p>Product Support</p>	<p>Warranty</p> <p>Support</p>	<p>Lifetime (online registration required)</p> <p>Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team</p>
<p>Additional</p>	<p>OEM option</p> <p>Made In</p> <p>Customisable</p>	<p>Available for bulk buy OEM</p> <p>Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"</p> <p>Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com</p>