

MIP3F Form Feed Printer

MIP3F Fixed Mount Friction Feed Printer

MIP3F Fixed Mount Friction Feed Printer

For in-vehicle use, this compact printer can also be mounted in a variety of locations. Its compact size makes it suitable for use in law enforcement and other mobile applications where single sheet or individual multi-part forms are used.

Easy Ribbon Changing

The 2 Million character cassette utilizes a reinker to achieve a compact size and provides consistent print quality throughout its life. A precision ribbon shield makes loading easy, quick and convenient.

Easy Paper Loading

To make paper loading fast and simple, the print mechanisms used in the MIP3X tractor feed printers is moved out of the way during paper loading, providing direct access to the tractors. Paper loading in the MIP3F friction feed unit is made simple by use of a paper guide where the form is easily slid into its print position.



Product Highlights:

- In-vehicle use.
- Mounted in a variety of locations.
- Suitable for use in law enforcement
- Single sheet or individual multi-part forms

MIP3F Form Feed Printer

Print Speed 288 cps @ 12 cpi
Print Method serial impact
Resolution NA
Character Density 10, 12, 15, 17 cpi
Standard Connectivity RS-232 and Bluetooth; or RS-232 and Wireless Ethernet 802.11b; or RS-232 and USB; or RS-232 and Centronics parallel
Standard Emulation IBM® Proprinter with Epson® Commands
Fonts Pica, Elite, Proportional, Prestige, Quadro, Brougham, Gothic

Consumables (Black) 2 million characters ribbon
STD Paper Handling Open mechanism for easy paper loading on tractor units; insertion slot for friction drive unit.
Number of Copies Original plus three copies
Forms Thickness max thickness 0.014"
Paper Type Continuous forms
Paper Size Width 3-8.5 (76-216mm); Length 4 in. or more (102mm)

Physical Weight 5.3 lbs (2.4 kg)
PhysicalSize 5.4" x 15" x 4.3"
Power Voltage 12/24 VDC Nominal, 10.5 - 30 VDC
Compliance Energy Star; Ozone-free; Class A of FCC Part 15B
Drivers Windows XP, 2000, 98, 95, NT 4.0. Use the Windows resident Epson Compatible 9 Pin driver (Epson FX equivalent)
Temperature 14° to 104° F (-10° to 40° C); Storage: -22° to 158° F (-30° to 70° C)
Acoustic NA
Warranty One Year Return To Depot

Option 1 Stand with paper tray and mount - for vehicle wall; Stand with paper tray and mount - for vehicle shelf
Option 3 Cigarette Lighter Adapter
Option 3 A/C Universal Power Supply, 100-240 VAC, 50-60 Hz.
Options 4 replacement 12 V DC Cable

Available Configuration MIP3F - RS232, Bluetooth
MIP3F - RS232, 802.11
MIP3F - RS232, Parallel
MIP3F - RS232, USB



Genicom Printer Outlet
1-866-430-6202
www.tgprinteroutlet.com

Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice. Copyright © 2007 TallyGenicom, L.P.

Genicom Printer Outlet.Com
1-866-430-6202

Fax for a Quick Quote
817-430-6250

Choose Model:

MIP3F Form Feed Printer

Organization _____

Name _____

Phone (_____) _____ Fax Number (_____) _____

E-Mail _____

Address _____

City _____ State _____ Zip _____

Please indicate your specifications or requirements:

Additional Comments:
