

VG2028wm

ENHANCE PRODUCTIVITY AND ENTERTAINMENT

Multimedia performance for your business



- > **Multi-functional base design (360° swivel, height adjustment)**
VESA compliant wall-mount interface and detachable base for ergonomic flexibility with 3.1 height, tilt and 360° swivel adjustments.
- > **USB hub**
2-port USB hub provides easy connectivity for USB devices.
- > **Multimedia enhanced**
Stereo speakers provide clear and rich sound.
- > **Widescreen aspect ratio with 1600 x 900 resolution**
The widescreen aspect ratio allows you to view Full HD content in its native format with no stretching or distortion.
- > **OptiSync® digital/analogue inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Eco-mode**
Environmentally-friendly Eco-mode reduces power consumption and extends backlight life.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.

Model Name	VG2028wm	
LCD	Size Optimum Resolution Brightness (cd/m ²) Contrast Ratio (typical) Dynamic Contrast Ratio Viewing Angle Response Time (ms) Pixel Pitch (HxV) Panel Surface Light Source (Hours) Color Support	20" wide Color TFT Active Matrix LCD 1600 x 900 300 cd/m ² (typical) 1000:1 static (typical) 100,000:1 170° (H), 160° (V) @ 10:1 contrast ratio 5ms (typical) 0.277mm (H) x 0.277mm (V) Anti-Glare Long life, 50,000 hrs. (typical) 16.7 M
INPUT	Analogue Sync Frequency (Fh / Fv)	RGB Analogue (75 ohms, 0.7/1.0 Vp-p) H/V Separated Fh: 24-82kHz, Fv: 50-75Hz
COMPATIBILITY	PC Mac	VGA up to 1600 x 900 non-interlaced Power Mac™ up to 1600 x 900
CONNECTOR	Analogue Digital Audio USB Power	1 x 15-pin mini D-sub 1 x DVI-D 1 x 3.5 mm audio in 2 x down stream, 1 x up stream Built-in power adapter, 3-Pin plug
SPEAKER POWER	Speaker Voltage Consumption (W) Save mode (W) ECO mode	2 x 2-watt AC 100-240V (Universal); 50/60Hz(Switch) 27 (typical) ≤1W 25W (Optimize) / 18W (Conserve)
CONTROLS	Basic OnView / OSD	Power, Mute, [1], Up [▲], Down [▼], [2] Auto Image Adjust, Contrast/Brightness, Audio adjust: Volume mute, Color Adjust: sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B], Information, Manual Image Adjust: Horizontal size, H/V position, fine tune, sharpness, dynamic contrast, aspect ratio, Eco mode, Setup Menu: Language select, resolution notice, OSD position, OSD time out, OSD background, Memory recall
OPERATING CONDITIONS	Temperature Humidity (Non condensed)	41° F - 95° F (5°C-35° C) 20 - 80% (non-condensing)
DIMENSIONS (WxHxD)	Physical (w/ stand)	481.2mm (W) x 393.4mm (H) x 230mm (D)
WEIGHT REGULATIONS	Net (w/ stand)	10.56 lb. (4.8 kg) CB, TCO03, WEEE, ROHS, ERGO, CE, Ukraine GOST-R+Hygienic ,SASO, BSMI, PSB, C-TICK, MIC (or KCC), Green Mark
WALL MOUNT (mm)	VESA® Mount Compliant	VESA 100mm x 100mm