

Multimedia Base /USB Hub

- **Multimedia Base (Stealth Black 6G3B12, Mist White 6G3B11)**

Powerful 36 W PMPO stereo sound output Bass Boost for extra enhancement
Headphone connector for personal listening Microphone connector for recording and videoconferencing

- **USB Hub (PCUH411)**

Connect up to 127 USB devices simultaneously. 1 upstream port and 4 downstream ports
Self-powered or bus-powered operation Fulfills USB-IF specification Rev. 1.1 Stands alone or clips on monitor base of Philips monitors.



6G3B12 Multimedia Base



USB Hub
Attached to
Multimedia Base



USB Hub Attached to
Standard Base



Multimedia Base
Attached to
Standard Base



6G3B11 Multimedia Base



PCUH411 USB Hub

Product Number 6G3B12 (Stealth Black)
6G3B11 (Mist White)

Technical Specifications

Amplifier

- RMS power 3 W Stereo Audio (1.5W/channel, RMSx2, 140 Hz-20 kHz, 4 ohms, 1% THD)
- Input signal level 340 mV RMS
- Bass boost

Speakers

- Unit Diameter 2"
- Impedance 4Ω
- Frequency Response 140Hz-20kHz
- Dual Passive Bass Pipes

Option

USB Hub PCUH411 Clip-On Option

Adapter

- Input (6G3B11/00) 207~253 VAC, 50 Hz
(6G3B11/74) 108~132 VAC, 60 Hz
- Output 9 VDC, 600 mA

Regulatory Approvals

- UL • CSA
- CE • TCO '99



Connections and Cables

- Headphone Connection 3.5 mm jack
- Microphone Input 3.5 mm jack
- Microphone Output 3.5 mm jack
- Audio Cable 1.8M, 3.5 mm jack to 3.5 mm jack

Physical Specifications

- UPC Code 6G3B12 (Stealth Black) 0 37849 92463 1
6G3B11 (Mist White) 0 37849 89587 0
- Dim. (Excl. Swivel)(WxHxD)(inch) 9.4" x 2.1" x 8.2"
- Dim. (Excl. Swivel)(WxHxD)(mm) 239 mm x 54 mm x 208 mm
- Additional Height for Monitor 1.1"/28 mm
(Multimedia Base-Normal Base)
- Weight 2.0 lbs./0.9 kg
- Additional Weight for Monitor 1.1 lbs./0.5 kg
(Multimedia Base-Normal Base)
- Power Consumption 5 Watts
- Carton Dimensions (WxHxD)(inch) 12.8" x 9.8" x 4.5"
- Carton Dimensions (WxHxD)(mm) 239 mm x 54 mm x 208 mm
- Carton Weight 3.1 lbs./1.4 kg

Product Number PCUH411 (USB Hub)

Technical Specifications

Device Support

- All USB Products
- Up to 127 Devices Simultaneously

Standards

- USB-IF Specification Rev. 1.1

Bandwidth

- 1.5 Mbps for Unshielded Cable
- 12 Mbps for Shielded Cable

Ports

- 4 Downstream Ports
- 1 Upstream Port

Over-Current Protection

- On Each Downstream Port

Power Source

- Self-Powered via Power Supply
- Bus-Powered from PC
- Maximum per Port Current 500 mA (when using power supply)

Power Consumption

- Operating Current 65 mA

Power Supply

- Input 100~240V, 1.0A max., 50~60Hz, 28~40VA
- Output +5V, 2.6A

LED Indicators

- Green/On = Link/Active Port
- Green/Off = Over-Current or Alert

Regulatory Approvals (Version Dependent)

- CE • CSA
- FCC • C-Tick
- UL • T-mark

Environment

- Operation Temperature 0°C to 70°C
- Humidity 0% - 80% RH Non-Condensing

Physical Specifications

- UPC Code 0 37849 89681 5
- Weight .4 lbs./150g
- Dim. With Cover (WxHxD)(inch) 5.3" x 1.0" x 2.8"
- Dim. With Cover (WxHxD)(mm) 136 mm x 25 mm x 72 mm
- Dim. Without Cover (WxHxD)(inch) 5.3" x 1.0" x 2.1"
- Dim. Without Cover (WxHxD)(mm) 136 mm x 25 mm x 55 mm
- Carton Dimensions (WxHxD)(inch) 10.0" x 7.2" x 2.7"
- Carton Dimensions (WxHxD)(mm) 255 mm x 183 mm x 68 mm
- Carton Weight 1.5 lbs./0.7 kg

INTERNET ADDRESS:

TECHNICAL SUPPORT:

<http://www.philips.com>

(877) 835-1838 (USA)

(903) 242-4804 (outside USA)

Specifications subject to change
without notice.

Printed in the U.S.A., ©2003 Philips
Consumer Electronics Co. A Division of
Philips Electronics North America
Corp. As an Energy Star partner, Philips
has determined that this product meets the
Energy Star guidelines for energy efficiency.
All trademarks acknowledged. Copyright
2001 Koninklijke Philips Electronics N.V.
CCM-110-01/03

Literature Order Number:

6G3B11/6G3B12/PCUH411

Compatibility:

For Multimedia Base and USB Hub compatibility
with monitors, refer to chart below. (The USB Hub
can be used stand alone or attached to the
6G3B11 or 6G3B12 Multimedia Base.)

Model	6G3B11	6G3B12	PCUH411
CRT			
105Exx	•	•	•
107Exx	•	•	•
107Bxx	•	•	•
107Pxx	•	•	•
107Txx	•	•	•
109Sxx	•	•	•
109Bxx	•	•	•
109Pxx			•
201Bxx			•
202Pxx			•
LCD			
150S2x			•
150S3x			•
150B2x			•
150B3x			•
150P2x			•
150P3x			•
170B2x			•
180B2x			•
180P2x			•

