



1619Sw

Cabinet Color	All Glossy Black
Panel	TFT Active Matrix LCD 16" Widescreen, Diagonal VIS: 15.6" Widescreen , Diagonal Hard Coating, Anti-glare Treatment
Pixel Pitch	0.252mm (H)x0.252mm(V)
Display Area	344.2mmx193.5mm
Brightness	250 cd/m2 (typ)
Contrast Ratio	1500:1 (DCR)
Response Time	8ms (typ)
Viewing Angle	Horizontal: 90 Degrees (CR>10) Vertical: 45 Degrees (CR>10)
Compatibility	VESA VGA,XGA,SVGA,WXGA Mac® Equipped With Analog VGA Dsub
Scanning Frequency	Horizontal: 30K~60KHz Vertical: 50~75 Hz
Pixel Frequency	85MHz
Maximum Resolution	1366x768@60Hz
Recommended Resolution	1366x768@60Hz
Resolutions Supported	640x350@70,640x480@60/72/75,720x400@70, 800x600@60/75,832x624@74.5,1280x720@60,1360x768@60
Color	16.7 Million
Signal Input	Video: 0.7Vp-p, RGB Analog Separate Sync: TTL Level H/V Sync: Positive / Negative
Connectors	RGB Signal: 15-pin D-sub (3-Pin Plug CEE22)
Power Source	Universal 100~240VAC, 50/60Hz,
Power Consumption	28W Max
Plug & Play	DDC 1/2B/CI
EPA ENERGY STAR®	Yes
User Control	AUTO, Left, Right, Menu, Power
OSD Function	Brightness, Contrast, Eco Mode, Gammar,DCR,H/V Position, Phase, Clock, Color Temperature, Color Boost,Picture Boost, OSD Language Selection, Timeout, Menu Position, Auto Config, DDC-CI, Reset, Information
Language Supported	English, Spanish, French, Portuguese, German, Russian, Italian, Simple Chinese
Compliance	CCC/cUL/FCC/CE/TUV-S/EPA,Windows Vista
Other Features	VESA 75mm Wall Mountable*, Aesthetic iconic OSD, 5-scene Dynamic Color Boost
Dimensions (WxHxD mm)	376x304x190mm
Dimensions (WxHxD inches)	14.8x12.0x7.5in
Carton (WxHxD inches)	17.2x11.9x4.6in
Weight	5.94 Lbs (2.7kgs) Net 8.14 Lbs (3.7kgs) Gross
Loading Qty w/pallet	20' = 1632 pcs.; 40' Std = 3536 pcs.
UPC Code	685417019380

Note: Specifications are subject to change without notice. *Wall mount arm & bracket not included.

Windows Vista and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. A01/08