

Bush Hog® TOUGH

3414 Series Rotary Cutters

BUSH HOG® TOUGH FEATURES

TOUGH 10 Gauge Deck Construction

TOUGH 7 Gauge Strongbacks

TOUGH 1/4 Inch Sidebands

TOUGH Rubber Cushioned Axle Arms

TOUGH Round Blade Pan Or Straight Bar

TOUGH 5 Year Gearbox Limited Warranty

TOUGH Powder Coat Paint



3414

MODELS	
Cutting Width	14 ft
Cutting Capacity	2 1/2 inch diameter
Dimensions (width x length)	14 ft 7 inches x 9 ft 1 inch (Lift), 14 ft 7 inches x 13 ft 5 inches (Pull)
Transport Width	14 ft 8 inches
Type Hitch	3 Point Cat. II & III Standard & Quick Hitch, Cat. II & III (Semi-Mount) and Center Pull Self Leveling
Cutting Height	2 to 13 inches
Deck Thickness	10 gauge
Side Bands	1/4 x 10 inches
Minimum Tractor HP	90 PTO (Lift), 75 PTO (Pull)
Driveline	ASAE Cat. 5 (For 540 RPM Lift, Pull and Semi-Mount), ASAE Cat. 4 (For 1000 RPM Pull Models)
Cross Shafts	ASAE Cat. 5 Rubber Element or Optional Cat. 4 Shear Pin/Rubber Element
Gearbox HP	(3) 205 - Center, 190 - Outboard
Tractor PTO Speed	540/1000 RPM
Driveline Protection	4 Plate PTO Slip Clutch
Height Adjustment	Choice of Manual Height Bundle or Hydraulic
Blade Holder(s)	Straight or Round
Blades	1/2 x 4 inches - Uplift
Blade Tip Speed	15,242 FPM
Tires	Laminated, Pneumatic, Aircraft
Spring Cushioned Axles	Rubber Cushioned, Choice of Single or Dual on Pull and Semi-Mount Models
Deflectors	Front Belting and Rear Band, Optional Chains
Safety Tow Chain	Standard for Pull Models
Approximate Weight (Pull with Single Axle)	3383 lbs
Highway Lighting	Standard
Options	Chain Shielding, Shredder Attachment, Third tailwheel for Lift or Semi-Mount Models
Warranty	1 year limited warranty with a 5 year gearbox limited warranty