

# LUMIÈRE®




## ASPEN 1900-AA

39W (max) PAR20 Metal Halide

50W (max) MR16 Halogen  
Low Voltage (12V)

### FEATURES

- Includes anchor bolts & template
- Adjustable aperture w/ locking mechanism
- Patented LumaLevel™ mounting/leveling system
- Machined aluminum housing, cast base
- Stainless steel hardware
- UL / cUL listed
- Three (3) year warranty



SAMPLE NUMBER: 1900-AA-24-MH39PAR20-120-BK

MODEL	SIZE	SOURCE	VOLTS	FINISH	OPTIONS
1900-AA Adjustable aperture	24	<i>Metal Halide</i> <b>MH39PAR20</b> 39W / PAR20 / medium <i>Includes integral core &amp; coil ballast. Lamp not included.</i>	<b>120, 208</b> <b>240, 277</b> <b>347</b>	<i>Painted</i> <b>BK</b> Black <b>BZ</b> Bronze <b>CS</b> City silver <b>VE</b> Verde <b>WT</b> White	<b>EL</b> Electronic HID ballast (120/277V) in lieu of core & coil <b>IT</b> Integral transformer for 12V MR16 source <i>See "Accessories &amp; Technical Data" section of catalog for remote transformers</i>
	30	<i>Halogen</i> <b>50MR16</b> 50W / MR16 / GU5.3 <i>12V remote or integral transformer required - not included Lamp not included</i>	<b>120/12</b> <b>277/12</b>		
<i>To ship anchor bolt/template kit in advance</i> <b>LAB</b> Less anchor bolts & template (order kit separately - 7048PK)					




## ASPEN 1900-OA

39W (max) PAR20 Metal Halide

50W (max) MR16 Halogen  
Low Voltage (12V)

### FEATURES

- Includes anchor bolts & template
- Open (fixed) aperture
- Patented LumaLevel™ mounting/leveling system
- Machined aluminum housing, cast base
- Stainless steel hardware
- UL / cUL listed
- Three (3) year warranty



SAMPLE NUMBER: 1900-OA-24-MH39PAR20-120-BK

MODEL	SIZE	SOURCE	VOLTS	FINISH	OPTIONS
1900-OA Open aperture	24	<i>Metal Halide</i> <b>MH39PAR20</b> 39W / PAR20 / medium <i>Includes integral core &amp; coil ballast. Lamp not included.</i>	<b>120, 208</b> <b>240, 277</b> <b>347</b>	<i>Painted</i> <b>BK</b> Black <b>BZ</b> Bronze <b>CS</b> City silver <b>VE</b> Verde <b>WT</b> White	<b>EL</b> Electronic HID ballast (120/277V) in lieu of core & coil <b>IT</b> Integral transformer for 12V MR16 source <i>See "Accessories &amp; Technical Data" section of catalog for remote transformers</i>
	30	<i>Halogen</i> <b>50MR16</b> 50W / MR16 / GU5.3 <i>12V remote or integral transformer required - not included Lamp not included</i>	<b>120/12</b> <b>277/12</b>		
<i>To ship anchor bolt/template kit in advance</i> <b>LAB</b> Less anchor bolts & template (order kit separately - 7048PK)					




## ASPEN 1900-IL

42W (max)  
Compact Fluorescent  
Line Voltage

### FEATURES

- Includes anchor bolts & template
- Low glare internal lens louver
- Patented LumaLevel™ mounting/leveling system
- Machined aluminum housing, cast base
- Stainless steel hardware
- UL / cUL listed
- Three (3) year warranty



SAMPLE NUMBER: 1900-IL-24-CF42-120-BK

MODEL	SIZE	SOURCE	VOLTS	FINISH	OPTIONS
1900-IL Internal louver	24 30	<i>Compact Fluorescent</i> <b>CF42</b> 26W, 32W, or 42W / triple tube / universal GX24q <i>Includes integral universal electronic ballast (120-277V) Lamp not included</i>	<b>120, 208</b> <b>240, 277</b>	<i>Painted</i> <b>BK</b> Black <b>BZ</b> Bronze <b>CS</b> City silver <b>VE</b> Verde <b>WT</b> White	<i>To ship anchor bolt/template kit in advance</i> <b>LAB</b> Less anchor bolts & template (order kit separately - 7048PK)