



Hustler Commercial Engines Specifications

Large frame, commercial products including: Hustler Z, Super Z, and ATZ.

	Honda	Kawasaki	Kawasaki	Kawasaki	Kawasaki	Kawasaki
Horsepower	24	23	25	26 LC	29	31
No. of Cylinders	2	2	2	2	2	2
Displacement	670 cc	675 cc	675 cc	675 cc	852 cc	852 cc
Compression Ratio	8.3:1	8.1:1	8.1:1	8.6:1	8.2:1	8.2:1
Max. Torque	37.5 FT lbs @2500 RPM	39.8 FT lbs @2400 RPM	41.0 FT lbs@2400 RPM	42.7 FT lbs @2400 RPM	53.2 FT lbs @2200 RPM	54.3 FT lbs @2400 RPM
Starter	12 volt	12 volt	12 volt	12 volt	12 volt	12 volt
Ignition	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Charging System	12-volt, 20-amp	12-volt, 15-amp	12-volt, 15-amp	12-volt, 20-amp	12-volt, 15-amp	12-volt, 15-amp
Governor	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Cooling	Air	Air	Air	Liquid	Air	Air

	Kohler	Kohler	Kohler	Shibaura
Horsepower	27	28 EFI	30	25
No. of Cylinders	2	2	2	3
Displacement	725 cc	725 cc	747 cc	1131 cc
Compression Ratio	9.0:1	9.0:1	9.4:1	23.5:1
Max. Torque	42.0 FT lbs @2800 RPM	44.3 FT lbs @2400 RPM	47.1 FT lbs @2600 RPM	48.7 FT lbs @2200 RPM
Starter	12 volt	12 volt	12 volt	12 volt
Ignition	Electronic	Electronic	Electronic	Compression
Charging System	12-volt, 20-amp	12-volt, 25-amp	12-volt, 20-amp	12-volt, 40-amp
Governor	Mechanical	Mechanical	Mechanical	Mechanical
Cooling	Air	Air	Air	Liquid



For more information: www.hustlerturf.com

HUSTLER

HUSTLER TURF EQUIPMENT • HESSTON, KANSAS 67062 • 1-800-395-4757