



1/2" Impact Wrench

TL1102

- 275 ft. lbs. of torque for fast removal of lug nuts and bolts in overall automotive service, bodyshop, farm and light truck work
- Forward/reverse switch for one-handed directional changes
- Patented balanced ergonomic design for comfort during continuous use
- Patented single hammer impact mechanism provides 20% more working torque
- Exhaust diffuser for quiet operation



5.4 AVG. SCFM Requirement @ 90 PSI

1/2" Impact Wrench

TL0502

- 250 ft. lbs. ultimate torque
- Built-in power regulator to control speed and torque
- Push button forward/reverse valve for fast change of direction



5.1 AVG. SCFM Requirement @ 90 PSI

3/8" Impact Wrench

TL1149

- 130 ft. lbs. ultimate torque
- 1,200 impacts per minute
- Patented single impact mechanism provides 20% more working torque
- Balanced, compact, ergonomic design for increased comfort



4.5 AVG. SCFM Requirement @ 90 PSI

Why Use Air Powered Equipment?

Finish your automotive and woodworking projects faster and easier with the benefits of air power. Air tools provide more power than electric tools. Air tools are lighter and more compact compared to their electric counterpart. They are easier to maintain and operate with fewer moving parts. Air tools also operate at cooler temperatures. Experience the benefits of Campbell Hausfeld® air tools including ergonomic designs and high performance for tough jobs.

1/2" Impact Wrench

TL1302

- 350 ft. lbs. ultimate torque
- 850 impacts per minute
- Powerful and balanced twin hammer impact mechanism for maximum output and smooth operation
- Ergonomic design for increased comfort

4.8 AVG. SCFM Requirement @ 90 PSI

NEW



1/2" Impact Wrench

PL150296

- 380 ft. lbs. ultimate torque
- 1,000 impacts per minute
- Heavy-duty square drive for automotive, farm and light truck work
- Powerful pin clutch mechanism for balanced operation

5.1 AVG. SCFM Requirement @ 90 PSI



1/2" Impact Wrench

PL250298

- 450 ft. lbs. ultimate torque
- 1,200 impacts per minute
- Powerful and balanced twin hammer impact mechanism for maximum output and smoothness
- Adjustable power regulator for both forward and reverse directions

5.1 AVG. SCFM Requirement @ 90 PSI



1/2" Impact Wrench (2" anvil)

PL255698

- Alloy and cast iron components
- 2" extended anvil
- Variable power regulator and forward/reverse
- Muffled handle exhaust

5.1 AVG. SCFM Requirement @ 90 PSI



3/4" Impact Wrench

PL1586

- 1,000 ft. lbs. of torque, provides power to remove and replace fasteners on semi-trucks and other large vehicles
- Two piece housing for ease of service
- Pistol grip handle provides comfort during use
- Powerful pin clutch mechanism for balanced operation

6.1 AVG. SCFM Requirement @ 90 PSI



Impact Wrenches & Ratchets



3/8" Butterfly Impact Wrench

TL1017

- 75 ft. lbs. ultimate torque
- 1,000 impacts per minute
- Great for small fastener work in engine and body repairs
- Includes swivel air inlet connection



2.4 AVG. SCFM Requirement @ 90 PSI

1" Impact Wrench

PL1557

- 1,100 ft. lbs. ultimate torque
- 600 impacts per minute
- 1/2" NPT air inlet
- Superior construction for truck tire work and heavy equipment service
- Two stage air compressor is required



17.5 AVG. SCFM Requirement @ 90 PSI

1/4" Ratchet

TL1147

- 25 ft. lbs. of torque for fast removal and installation of nuts and bolts in dashboard work
- Ball socket retainer provides fast and easy socket replacement
- Smaller than a standard 3/8" air ratchet, for use in tighter more compact areas



4.1 AVG. SCFM Requirement @ 90 PSI

1/4" Ratchet

PL1547

- At 18 ft. lbs. of torque, provides the power to remove and install small nuts and bolts in under the dashboard work, small engine repair and bodywork
- Ball socket retainer provides fast and easy socket replacement
- Small size allows for reach into areas that a conventional 3/8" ratchet could not reach



3.2 AVG. SCFM Requirement @ 90 PSI

3/8" Ratchet

TL1001

- At 50 ft. lbs. of torque, provides the power to remove and install nuts and bolts
- Ball socket retainer provides fast and easy socket replacement



4.8 AVG. SCFM Requirement @ 90 PSI

3/8" Ratchet

TL1101

- At 25 ft. lbs. of torque, provides the power to remove and install nuts and bolts
- Ball socket retainer provides fast and easy socket replacement
- Smaller than a standard 3/8" air ratchet, allows for use in tighter more compact areas



4.1 AVG. SCFM Requirement @ 90 PSI

3/8" Ratchet

PL150198

- At 55 ft. lbs. of torque, provides the power to remove and install nuts, bolts and spark plugs during engine repair, tune-ups and radiator work
- Heat treated ratcheting components for increased durability
- Soft Santoprene® elastomer grip provides increased comfort during continuous use



4.8 AVG. SCFM Requirement @ 90 PSI

1/2" Ratchet

PL1548

- 90 ft. lbs. of torque provides the power to remove and install large fasteners on outboard engines, tractors and other heavy machinery
- Ball socket retainer provides fast and easy socket replacement
- Extra long handle provides better handling during operation and additional power for stubborn fasteners



8.0 AVG. SCFM Requirement @ 90 PSI

Die Grinders



Die Grinder

TL1120

- 25,000 RPMs provides the speed for grinding, porting, smoothing, general polishing and deburring
- Patented lightweight engineered composite housing reduces fatigue and protects against cold temperatures
- Ideal for use on a variety of materials including: wood, metal, plastic, ceramic and cast iron
- Standard 1/4" collet for all types of accessories
- Exhaust diffuser for quiet operation

 **6.2** AVG. SCFM Requirement @ 90 PSI



Full Size Die Grinder

TL1121

- At 22,000 RPMs, provides the speed to grind, port, smooth, polish and deburr most materials including wood, metal, plastic, ceramic and cast iron
- 1/2 horsepower motor provides more power than a standard die grinder
- Patented lightweight engineered composite housing reduces fatigue and protects against cold temperatures
- Standard 1/4" collet for all types of accessories
- Exhaust diffuser for quiet operation

 **10.7** AVG. SCFM Requirement @ 90 PSI



Die Grinder

PL1520

- 25,000 RPMs
- Great for high speed grinding, porting, smoothing, general polishing and deburring in medium duty work
- Compact size allows for use in confined areas
- Front exhaust

 **8.1** AVG. SCFM Requirement @ 90 PSI



Full Size Die Grinder

PL252199

- 25,000 RPM
- Great for high speed grinding, porting, smoothing, general polishing and deburring in medium duty work
- Compact size allows for use in confined areas
- Front exhaust

 **11.0** AVG. SCFM Requirement @ 90 PSI



Angle Die Grinder

TL1141

- 18,000 RPMs
- Pistol design is ideal for gasket removal and surface conditioning applications
- Extended trigger for ease of operation and increased comfort
- Patented balanced ergonomic design for increased comfort during continuous use

5.8 AVG. SCFM Requirement @ 90 PSI



Angle Die Grinder

PL154199

- At 18,000 RPMs, provides the speed to perform general grinding, porting, gasket removing, general polishing and deburring in confined areas
- Soft Santoprene® elastomer grip provides increased comfort during continuous use
- Includes 1/4" and 1/8" collets for all types of accessories

7.8 AVG. SCFM Requirement @ 90 PSI



4" Angle Grinder

PL1555

- At 11,000 RPMs, provides the power for fast material removal
- Ideal for cleaning, deburring, grinding and high amounts of rust or material removal
- Equipped with a side handle for better handling during operation accessories

11.0 AVG. SCFM Requirement @ 90 PSI



Cut-Off Tool

TL1135

- 20,000 RPMs provides the speed and power to cut through 1" diameter steel rods, fiberglass, copper/aluminum tubing, and angle iron up to 1/2"
- Adjustable swivel safety guard provides better safety and maneuverability
- Patented lightweight engineered composite housing reduces fatigue and protects against cold temperatures
- Trigger safety-lock mechanism prevents accidental start-ups
- Exhaust diffuser for quiet operation

11.8 AVG. SCFM Requirement @ 90 PSI



Cut-Off Tool


PL253599

- At 23,000 RPMs, provides the speed and power to cut through 1" diameter steel rods, fiberglass, copper/aluminum tubing, and angle iron up to 1/2"
- 3/4 horsepower motor provides more power than a standard cut-off tool
- Soft Santoprene® elastomer grip provides increased comfort during continuous use
- Built-in power regulator to control speed in detail cutting
- Equipped with guards and safety catches to prevent injury

11.5 AVG. SCFM Requirement @ 90 PSI



Cutting Tools



Air Nibbler

PL1519

- At 3,800 strokes per minute, provides the cutting power to cut up to 16 gauge steel
- Designed to cut intricate patterns in sheet metal and aluminum without leaving burrs

7.8 AVG. SCFM Requirement @ 90 PSI



Reciprocating Saw

PL1540

- At 10,000 strokes per minute, provides the cutting power to cut up to 16 gauge steel
- Designed to cut plastic, aluminum, fiberglass and sheet metal on flat and curved surfaces
- Equipped with safety latch to prevent accidental starts

1.5 AVG. SCFM Requirement @ 90 PSI



Punch/Flange Tool

PL1550

- 5 mm punch diameter, 1/2" flange depth
- Prepares sheet metal for riveting, brazing or welding

0.1 AVG. SCFM Requirement @ 90 PSI



Metal Shear

PL1543

- At 2,500 strokes per minute, makes clean cuts into 18 gauge cold rolled steel
- Designed to cut angles and squares in sheet metal, aluminum, rubber and plastic
- Great for duct work and autobody repair

6.7 AVG. SCFM Requirement @ 90 PSI



1 5/8" Stroke Hammer

TL1103

- 1 5/8" (41 mm) stroke provides the power for general cutting, chipping and scraping
- Cuts, chips and scrapes most materials and is used for light duty automotive exhaust removal, front-end work and masonry
- Patented balanced, lightweight, ergonomic design provides increased comfort and reduces fatigue
- Includes 2 chisel bits

6.0 AVG. SCFM Requirement @ 90 PSI



2 5/8" Stroke Hammer

PL153499

- 2 5/8" (67 mm) stroke provides the power for panel cutting and other cutting needs
- Cuts, chips and scrapes most materials and is used for medium duty automotive exhaust removal, front-end work and masonry
- Soft Santoprene® elastomer grip provides increased comfort during continuous use
- Built-in power regulator to control speed during use

11.0 AVG. SCFM Requirement @ 90 PSI



3 5/8" Stroke Hammer

PL2534

- 3 1/2" (89 mm) stroke provides the power for bolt cutting and other cutting needs
- Cuts, chips and scrapes most materials and is used for heavy-duty automotive exhaust removal, front-end work and masonry
- Equipped with quick connect chisel retainer for fast chisel changes

11.0 AVG. SCFM Requirement @ 90 PSI



INCLUDES QUICK CHANGE CHISEL RETAINER



3/8" Air Drill

TL1106

- 2,400 RPMs provides the speed to drill, hone, saw and wire brush most metal or wood materials
- Compact and maneuverable for demanding jobs
- Patented balanced ergonomic design provides increased comfort
- Extended trigger for ease of operation and increased comfort
- Lightweight engineered composite housing reduces fatigue

7.2 AVG. SCFM Requirement @ 90 PSI



Air Powered Drill

TL1006

- 2,300 RPMs provides the speed to drill, hone, and ream metal, wood, and concrete
- Compact and maneuverable for demanding jobs

5.5 AVG. SCFM Requirement @ 90 PSI



3/8" Reversible Drill

PL154599

- Used to drill, hone, saw and wire brush most metal or wood materials
- Durable Jacobs® chuck for reliable bit replacement
- Soft Santoprene® elastomer grip provides increased comfort during continuous use
- Reversible to assist when binding occurs and for replacing screws

9.2 AVG. SCFM Requirement @ 90 PSI





3/8" Keyless Chuck Reversible Drill PL254599

- Used to drill, hone, saw and wire brush most metal or wood materials
- Durable keyless Jacobs® chuck for fast and easy bit changes
- Reversible to assist when binding occurs and for replacing screws
- Soft Santoprene® elastomer grip provides increased comfort during continuous use

 **9.2** AVG. SCFM Requirement @ 90 PSI



3/8" Angle Drill PL1544

- Used to drill hone, ream, hole saw and wire brush most metal or wood materials
- Durable Jacobs® chuck for reliable bit replacement
- Angle head for use in confined areas

 **5.9** AVG. SCFM Requirement @ 90 PSI



1/2" Reversible Drill PL154699

- Used to drill, hone, saw and wire brush most metal or wood materials
- Durable keyless Jacobs® chuck for fast and easy bit changes
- Reversible to assist when binding occurs and for replacing screws
- Soft Santoprene® elastomer grip provides increased comfort during continuous use

 **10.7** AVG. SCFM Requirement @ 90 PSI



Dual Action Sander TL1004

- 10,000 RPMs
- Designed for sanding wood, metal, fiberglass and autobody fillers
- Best when used for blending and smoothing filler in light duty applications

 **10.0** AVG. SCFM Requirement @ 90 PSI



Dual Action Sander

PL150499

- 10,000 RPMs for swirl-free finishes
- Designed for sanding wood, metal, fiberglass and autobody fillers
- Soft Santoprene® elastomer grip provides increased comfort during continuous use
- Patented ergonomic design provides increased comfort during prolonged use

13.0 AVG. SCFM Requirement @ 90 PSI



7" Sander

PL1551

- 4,500 SPMs
- Designed to smooth welds, remove rust and remove body filler

15.1 AVG. SCFM Requirement @ 90 PSI



5" High Speed Sander

TL1118

- 18,000 RPMs provides the speed for rough material removal, weld smoothing, body filler removal and rough shaping of filler
- Lightweight engineered composite housing reduces fatigue
- Patented, balanced ergonomic design for increased comfort during operation
- Extended trigger for ease of operation and increased comfort
- Includes 3 back-up pads (3", 4 1/2" and 5 1/2") for varying applications

12.3 AVG. SCFM Requirement @ 90 PSI



Random Orbit Sander

PL1565

- 10,000 RPMs
- Ideal for sanding wood, body filler, fiberglass, metal and other surfaces
- Swirl-free, efficient fine finish sanding

11.6 AVG. SCFM Requirement @ 90 PSI



Random Orbit Sander with Self-Generating Vacuum System

PL1566

- 10,000 RPMs
- Ideal for sanding wood, body filler, fiberglass, metal and other surfaces
- Swirl-free, efficient fine finish sanding
- Self-generating vacuum bag to collect dust

11.6 AVG. SCFM Requirement @ 90 PSI



Jitterbug Sander

TL1005

- 8,000 SPMs
- Designed for sanding wood, metal, fiberglass and autobody fillers
- Palm trigger for easy on/off action

9.0 AVG. SCFM Requirement @ 90 PSI



19 Piece Tool Kit

TL1010

- Includes: 3/8" ratchet, 1/2" impact wrench, 1/2" impact sockets (1/2" 9/16", 5/8", 11/16", 10 mm, 12 mm, 15 mm, 17 mm, 19 mm, and 21 mm) 3/4"-13/16" SAE flip socket, 3/8" (F)-1/2" (M) socket adapter, 3" extension, (2) 1/4" industrial plugs, air tool oil, and carrying case

5.1 AVG. SCFM Requirement @ 90 PSI



15 Piece Tool Kit

TL1061

- Great for do-it-yourself projects
- Includes: 1/2" impact wrench, 1-5/8" stroke air hammer, 3/4"-13/16" SAE flip socket, 3" extension, (4) chisel bits, chisel spring retainer, blowgun, (3) 1/4" industrial plugs, air tool oil, and carrying case

6.0 AVG. SCFM Requirement @ 90 PSI



27 Piece Tool Kit

TL1063

- Perfect start-up kit for the home mechanic
- Includes: 3/8" ratchet, 1/2" impact wrench, siphon-feed spray gun, (2) 1/2" deep well impact sockets: 3/4", 13/16", (3) 1/2" shallow well impact sockets: 1/2", 9/16", 5/8", 3/8" (F)-1/2" (M) socket adapter, blowgun, (5) blow gun accessories, dual air chuck, tire gauge, 25' recoil hose, 1/4" NPT(F) industrial coupler, (4) 1/4" NPT(M) industrial plug, 1/4" NPT(F) industrial plug, PTFE thread sealant tape, air tool oil, and blow mold case

5.1 AVG. SCFM Requirement @ 90 PSI

**Not stocked as an everyday item*



Ratchet, Die Grinder Kit

TL1067

- Includes: 3/8" ratchet, 1/4" die grinder, (4) 3/8" impact sockets, (2) 1/4" grinding stones, 1/4" NPT(F) industrial coupler, (2) 1/4" NPT(M) industrial plugs, (2) die grinder wrenches, air tool oil, and blow mold case

6.0 AVG. SCFM Requirement @ 90 PSI



62 Piece Tool Kit

TL1069

- Includes: 1/2" impact wrench, 3/8" air ratchet, 1 5/8" stroke air hammer, (10) sockets, 3" extension bar, 3/8" socket-screw bit adapter, (20) screwdriver bits, (3) chisel bits, chisel retainer spring, 3/8" (F)-1/2" (M) socket adapter, 1/4" swivel adapter, 1/4" NPT(F) coupler, (5) 1/4" I/M plugs 1/4" NPT(M), 1/4" NPT(M) hose coupling, 1/4" NPT(F) hose coupling, blowgun, (6) blowgun accessories, 1/4" NPT tire chuck, pencil tire gauge, roll of PTFE thread sealant tape, bottle of air tool oil, 4 mm Allen wrench, blow molded case

6.1 AVG. SCFM Requirement @ 90 PSI

**Not stocked as an everyday item*



70 Piece Garage Tool Kit

TL1070

- Includes: 1/2" impact wrench, 3/8" air ratchet, 1 5/8" stroke air hammer, (17) impact sockets, 3" extension bar, 3/8" socket-screw bit adapter, (21) screwdriver bits, (4) chisel bits, chisel retainer spring, 3/8" (F)-1/2" (M) socket adapter, 1/4" NPT(F) coupler, (5) 1/4" I/M plugs 1/4" MPT(M), 1/4" NPT(M) hose coupler, 1/4" NPT(F) hose coupler, blowgun, (6) blow gun accessories, 1/4" NPT(F) tire chuck, pencil tire gauge, roll of PTFE thread sealant tape, bottle of air tool oil, 4 mm Allen wrench, and blow molded case



6.1 AVG. SCFM Requirement @ 90 PSI

**Not stocked as an everyday item*

Sandblasting Kit

AT1226

- Draws abrasives from bucket or bag
- Designed to remove rust, scale and paint as well as etch glass and weather wood
- Includes: sandblast gun with ceramic nozzle, 10' hose, steel pick-up tube and Allen wrench



11.5 AVG. SCFM Requirement @ 90 PSI

30 lb. Capacity Sandblaster

AT1251

- Hopper holds 30 lbs. of abrasive for approximately 50 minutes of blasting
- Shoulder strap for added mobility
- Designed to remove rust, scale and paint as well as etch glass and weather wood
- Includes: sandblast gun with ceramic nozzle, material hose and hopper



11.5 AVG. SCFM Requirement @ 90 PSI

60 lb. Capacity Sandblaster

AT1210

- Hopper holds 60 lbs. of abrasive for approximately 100 minutes of blasting
- Designed to remove rust, scale and paint as well as etch glass and weather wood
- Includes: sandblast gun with ceramic nozzle, material hose and hopper



9.0 AVG. SCFM Requirement @ 90 PSI

120 lb. Capacity Sandblaster

AT1211

- Hopper holds 120 lbs. of abrasive for approximately 200 minutes of blasting
- Wheels provide added mobility
- Includes: gun with ceramic nozzle, material hose, hopper, and wheels



9.0 AVG. SCFM Requirement @ 90 PSI