70-1722 INSTRUCTIONS FOR AMPLIFIED SOUND SYSTEMS



For vehicles with factory amplifiers:

In order to turn on the factory amplifier you must locate the 20-way harness that was plugged into the factory radio. In pin 16 in vehicles without navigation or pin 20 in vehicles with navigation (see diagram on reverse side) there is a Light Blue wire that you must attach to the Amp Turn On wire of the aftermarket radio for the amplifier to turn on.

Use Metra's standard wiring instructions for the remainder of the installation.

(See harness diagram on back of page) REV. 06/08/06 INST70-1722

70-1722 INSTRUCTIONS FOR AMPLIFIED SOUND SYSTEMS



For vehicles with factory amplifiers:

In order to turn on the factory amplifier you must locate the 20-way harness that was plugged into the factory radio. In pin 16 in vehicles without navigation or pin 20 in vehicles with navigation (see diagram on reverse side) there is a Light Blue wire that you must attach to the Amp Turn On wire of the aftermarket radio for the amplifier to turn on.

Use Metra's standard wiring instructions for the remainder of the installation.

(See harness diagram on back of page) REV. 06/08/06 INST70-1722

70-1722 INSTRUCTIONS FOR AMPLIFIED SOUND SYSTEMS



For vehicles with factory amplifiers:

In order to turn on the factory amplifier you must locate the 20-way harness that was plugged into the factory radio. In pin 16 in vehicles without navigation or pin 20 in vehicles with navigation (see diagram on reverse side) there is a Light Blue wire that you must attach to the Amp Turn On wire of the aftermarket radio for the amplifier to turn on.

Use Metra's standard wiring instructions for the remainder of the installation.

(See harness diagram on back of page)
REV. 06/08/06 INST70-1722

70-1722 INSTRUCTIONS FOR AMPLIFIED SOUND SYSTEMS



For vehicles with factory amplifiers:

In order to turn on the factory amplifier you must locate the 20-way harness that was plugged into the factory radio. In pin 16 in vehicles without navigation or pin 20 in vehicles with navigation (see diagram on reverse side) there is a Light Blue wire that you must attach to the Amp Turn On wire of the aftermarket radio for the amplifier to turn on.

Use Metra's standard wiring instructions for the remainder of the installation.

(See harness diagram on back of page) REV. 06/08/06 INST70-1722

70-1722 INSTRUCTIONS FOR AMPLIFIED SOUND SYSTEMS



For vehicles with factory amplifiers:

In order to turn on the factory amplifier you must locate the 20-way harness that was plugged into the factory radio. In pin 16 in vehicles without navigation or pin 20 in vehicles with navigation (see diagram on reverse side) there is a Light Blue wire that you must attach to the Amp Turn On wire of the aftermarket radio for the amplifier to turn on.

Use Metra's standard wiring instructions for the remainder of the installation.

(See harness diagram on back of page) REV. 06/08/06 INST70-1722

70-1722 INSTRUCTIONS FOR AMPLIFIED SOUND SYSTEMS



For vehicles with factory amplifiers:

In order to turn on the factory amplifier you must locate the 20-way harness that was plugged into the factory radio. In pin 16 in vehicles without navigation or pin 20 in vehicles with navigation (see diagram on reverse side) there is a Light Blue wire that you must attach to the Amp Turn On wire of the aftermarket radio for the amplifier to turn on.

Use Metra's standard wiring instructions for the remainder of the installation.

(See harness diagram on back of page) REV. 06/08/06 INST70-1722

70-1722 INSTRUCTIONS FOR AMPLIFIED SOUND SYSTEMS



For vehicles with factory amplifiers:

In order to turn on the factory amplifier you must locate the 20-way harness that was plugged into the factory radio. In pin 16 in vehicles without navigation or pin 20 in vehicles with navigation (see diagram on reverse side) there is a Light Blue wire that you must attach to the Amp Turn On wire of the aftermarket radio for the amplifier to turn on.

Use Metra's standard wiring instructions for the remainder of the installation.

(See harness diagram on back of page) REV. 06/08/06 INST70-1722

70-1722 INSTRUCTIONS FOR AMPLIFIED SOUND SYSTEMS



For vehicles with factory amplifiers:

In order to turn on the factory amplifier you must locate the 20-way harness that was plugged into the factory radio. In pin 16 in vehicles without navigation or pin 20 in vehicles with navigation (see diagram on reverse side) there is a Light Blue wire that you must attach to the Amp Turn On wire of the aftermarket radio for the amplifier to turn on.

Use Metra's standard wiring instructions for the remainder of the installation.

(See harness diagram on back of page) REV. 06/08/06 INST70-1722















