

# S-15E



▶ FEATURES

- Smart exterior with exceptional strength
- Foldable small footprint stand
- NeoV Optical Filter™
- Clear 400 contrast ratio
- Auto-adjustment for optimal setting
- Easy-to-use OSD
- Kensington® security slot
- VESA standard wall or arm mount



▶ SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD	
	<b>Panel Size</b>	15.0" (381mm)	
	<b>Max. Resolution</b>	XGA 1024 x 768	
	<b>Pixel Pitch</b>	0.297mm	
	<b>Brightness</b>	250cd/m <sup>2</sup> (Typical)	
	<b>Contrast Ratio</b>	400:1 (Typical)	
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment	
	<b>Viewing Angle (H/V)</b>	130°/100° (Typical)	
	<b>Display Color</b>	16.7M	
	<b>Response Time (R/F)</b>	7.5ms/17.5ms (Typical)	
Frequency (H/V)	<b>H:</b>	30kHz - 60kHz	
	<b>V:</b>	50Hz - 75Hz	
	<b>Max. Pixel Clock</b>	80MHz	
Life Time	<b>Life Time</b>	40,000hrs (Minimum)	
	<b>Input</b>	<b>Analog</b>	15-Pin D-Sub
Connector	<b>Power</b>	3-Pin AC Plug	
NeoV Optical Filter	<b>Thickness</b>	3.0mm (0.18")	
	<b>Reflection Rate</b>	<1%	
	<b>Transmission Rate</b>	>96%	
	<b>Hardness</b>	>6H (MOH's Rating)	
Tilt	<b>Tilt</b>	+5° ~ +20°	
Mounting	<b>VESA FPMPI</b>	Yes (75mm)	
Regulation Approval	<b>Safety &amp; EMI</b>	FCC, UL/CUL, EPA, TUV/GS, NORDIC, TCO 95, NUTEK, BSMI, VCCI, ISO 13406-2, CE, CB	
		<b>VESA</b>	DDC 1/2B, DPMS
		<b>Power</b>	<b>Power AC Consumption</b>
Dimensions	<b>Net (W x H x D)</b>	386 x 360 x 169mm (15.2" x 14.2" x 6.7")	
	<b>Packing (W x H x D)</b>	482 x 500 x 217mm (18.9" x 19.7" x 8.5")	
Weight	<b>Net Weight</b>	4.5Kg (9.9lbs)	
	<b>Gross Weight</b>	6.3Kg (13.9lbs)	
Packing	<b>1 Pallet</b>	40 Cartons	
	<b>20' Container</b>	480 Sets	
	<b>40' Container</b>	960 Sets	

All specifications are subject to change without prior notice.