



AFM-102 Harley USB Modem

Specification

Interface	USB 1.0 / 1.1
Connector Type	Client Side
Controller	Conexant Harley with Samrt DAA
Number of line	1
Telephone Jack Type	RJ-11
LED	2
Dialing	AA mode DTMF Tone
Command	AT Command set
Line Speed Data Mode	56000/53300/50667/49333/46667/45333/42667/41333/38667/37333/34667/33333/30667/29333/ 33600/31200/28800/26400/24000/21600/19200/16800/14400/12000/9600/7200/4800/2400
Terminal Speed	230400/115200/57600//38400/19200/12000/9600/7200/4800/2400/1200/300bps
Operation	Asynchronous
Protocols	ITU-T: V.92/V.90/V.34/V.32bis/V.32/V.22bis/V.22/V.21, BELL: 212A/103, K56flex
Operating Mode	Originate/Answer
Transmit Level	-6dBm to - 15dBm -10dBm(default)
Receive Level	-10dBm to -35dBm
Error Correction	MNP4 & V.42
Data Compression	MNP5, V.42bis & V.44
Flow Control	Xon/Xoff, RTS/CTS
Temperature	Operating: 0 ~ 70°C
Humidity	Operating: 0 ~ 85%
Power Voltage	From USB Port

PTT & Safety:

OS: Windows 9x/XP/NT4.0/2000/ME/Vista32 /64 / Linux

 FCC Part 15 & Part 68

Dimensions: 68 (L) * 25 (W) * 20 (H) mm

 CE