



CHRISTIE LX120

The Brightest LCD Projector

Uses

Staging applications

Large auditoriums
and churches

Executive briefing
and conference
centers

Training rooms

Medical training
theaters

Government
institutions

The Christie LX120 is the brightest LCD projector – bar none. With an incredible lumens and quad lamps, you get extremely powerful, high performance with a low operating cost. Perfect for large auditoriums and churches, executive briefing rooms and conference centers, an amazing 1300:1 contrast ratio ensures that every minute detail is sharp, clear and realistic.

The Christie LX120 gives you the connectivity to handle virtually any source and features a range of standard and optional analog and digital inputs from RGBHV through to DVI-I and HD-SDI. The Christie LX120 is compatible with standard video and HDTV formats. A complete range of optional lenses including short-throw fixed and long-throw zoom lenses with horizontal and vertical lens shift provide installation flexibility.

Configurable illumination to operate either in quad or dual lamp mode, you can maximize the lamp life and further reduce overall operating costs. As part of the Christie RoadRunner series, the Christie LX120 offers reliability, dependability and flexibility.

When you require brilliance combined with professional projection quality, the affordable Christie LX120 is your solution.

Christie LX120

Specifications



BRIGHTNESS

- 12,000 ANSI lumens (quad lamp)
- 6,000 ANSI lumens (dual lamp)
- Contrast ratio: 1300:1

DISPLAY TECHNOLOGY AND RESOLUTION

- 3-panel 1.8" p-Si LCD
- Native XGA 1024 x 768 resolution

STANDARD ACCESSORIES

- Real Colour Manager user-definable gamma software
- Wireless/wired remote controller (w/batteries)
- User's manual (CD-ROM & Quick Manual)
- Computer cable (Dsub15 to Dsub15)
- AC line cord (UL/European)

OPTIONAL ACCESSORIES

- 0.8:1, 1.2:1, 7.0:1 fixed lenses
- 1.1–1.5:1, 1.5–2.0:1, 1.3–1.8:1, 2.0–2.6:1, 2.6–3.5:1, 3.5–4.6:1, 4.6–6.0:1 zoom lenses
- ChristieNET™ networking and control system
- Ceiling mount
- Shipping case
- Lens mount adapter kit

OPTIONAL INPUT MODULES

- Dual SDI/HD-SDI module
- Warp & Blend module
- DVI digital interface module
- 5 BNC module
- Y/C interface module, S-video
- 15-pin sub-D interface module

With an option of lamp usage, the Christie LX120 offers the choice between projecting 12,000 lumens for stunningly bright images, or 6,000 lumens to extend the lamp life and provide built-in redundancy.

Corporate Offices

USA
10550 Camden Drive
Cypress, CA 90630
PH: 714-236-8610
FX: 714-503-3385
Toll free: 866-880-4462 (NA only)
sales-us@christiedigital.com

CANADA
809 Wellington Street North
Kitchener, Ontario N2G 4Y7
PH: 519-744-8005
FX: 519-749-3136
Toll free: 800-265-2171 (NA only)
sales-canada@christiedigital.com

Worldwide Offices

UNITED KINGDOM
PH: +44 118 977 8000
FX: +44 118 977 8100
sales-europe@christiedigital.com

GERMANY
PH: +49 2161 664540
FX: +49 2161 664546
sales-europe@christiedigital.com

FRANCE
PH: +33 (0) 1 47 48 28 07
FX: +33 (0) 1 47 48 26 06
sales-france@christiedigital.com

HUNGARY
PH: +36 (0)1 47 48 100
FX: +36 (0)1 47 48 452

SINGAPORE
PH: +65 6877 8737
FX: +65 6877 8747
sales-singapore@christiedigital.com

SHANGHAI
PH: +86 21 6278 7708
FX: +86 21 6270 5816
sales-china@christiedigital.com

BEIJING
PH: +86 10 6561 0240
FX: +86 10 6561 0546
sales-china@christiedigital.com

KOREA
PH: +82 2 702 1601
FX: +82 2 702 1602
sales-korea@christiedigital.com

JAPAN
PH: +81 3 3599 7481
FX: +81 3 3599 7482
sales-japan@christiedigital.com



Auto-set, on-screen displays, LED warning indicators and auto-adjusting power with either 110V or 220V models, makes the Christie LX120 easy to use.



The Christie LX120 offers reliability, dependability, flexibility and is compatible with a full array of video and data inputs.

INPUT SIGNAL COMPATIBILITY

- VGA through to UXGA (1600 x 1200)
- Accepts and displays all currently known DTV/HDTV formats (480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 1035i)

DIMENSIONS

- Weight: 80.3 lb (36.5 kg)
- Size: 22.8 W x 30.8 L x 9.9" H (581.2 x 783 x 9.9 mm)

POWER REQUIREMENTS

- Power consumption: 1800W maximum
Model #103-006101-01
- Line voltage: 110–120 VAC
- Operating current: 16A
Model #103-007101-01
- Line voltage: 200–240 VAC
- Operating current: 9A

INPUTS

- DVI-I
- 5 BNC: RGBHV/YpPr
- Composite video, S-Video
- D-Sub 15
- DB9 RS-232
- Wired remote jack

GRAPHICAL USER INTERFACE

- Auto set-up feature
- "Direct Access" intuitive user interface for complete projector control in twelve world languages
- Auto power-up feature

OPTICAL SYSTEM

- Fast Lens Change (FLC™) mount
- Power adjustable zoom, focus
- Up/down, left/right shift
- Image elevation up to 5.7"

LAMP

- Quad 300W lamps
- 1000 hours typical lamp life at maximum brightness
- User replaceable lamp

SCAN RATES

- Horizontal: 15–120 kHz
- Vertical: 50–120 Hz
- Pixel clock: 230 MHz

OPERATING ENVIRONMENT

- Temp: 5 to 35° C (40 to 95° F)
- Humidity: 20–80% non-condensing
- Altitude: 0–2700m (0–8858 ft)

AUDIBLE NOISE

- 51dB (auto fan control noise level reduction)

REGULATORY APPROVALS

- FCC Class A
- EN5502 Class A, CE
- RoHS and WEEE compliant
Model #103-006101-01
- CSA 22.2 No 950, UL 1950 cUL
Model #103-007101-01
- IEC950 (EN60950)

WARRANTY

- Product warranty: 3 years parts and labor (excluding lamp)
- Lamp warranty: 120 days or 500 hours (whichever comes first)