

speco technologies®

IP/Network Camera Infrastructure



IP-INTB1
2.8-10mm Auto Iris Bullet Camera

IP-INTB2
5-50mm Auto Iris Bullet Camera



IP-INTD3
2.8-10mm Auto Iris Dome Camera

IP-INTD4
5-50mm Auto Iris Dome Camera



IP-INTT5 Traditional Camera
Uses CS/CS Lenses

IP-T5
No Intensifier Feature

*IP Server and
Intensifier
In the Camera!*

*Access All Intensifier
Functions Over the
Internet or Network!*

- *View and record your cameras remotely over a network or the Internet*
- *Works with all LAN, WAN and Internet configurations*

Specifications

- Cameras have built-in web servers that work with Internet Explorer. No special software required for basic functionality and recording
- Linux Operating System built into camera – No virus threats
- Free DDNS Server
- Dual Streaming: Cameras have both MPEG-4 and JPEG CODECS which allow you to choose between streaming or high quality video
- Dome & bullet meet IP-67 standards
- Support of Dynamic and Static IP addresses
- Changeable/Selectable Ports allow one IP address to handle multiple cameras
- Premium software supplied at no extra cost for accessing advanced features
- Remotely view up to 16 cameras in one window...from anywhere in the world!
- Multiple levels of password protected remote access
- Includes advanced IP locator software to make system setup easy
- User adjustable settings for MPEG-4 and JPEG quality
- Built in motion detection
- Multiple Alarm handling capabilities
- RS-232 pass through for control of many popular Speed Domes
- Remotely upgradeable for software functions
- Schedule Recording, per camera, per day, per hour
- Selectable Resolutions: 704 x 480, 352 x 480, 352 x 240
- Protocols: HTTP, FTP, TCP/IP, DHCP, ARP, DNS, ICMP, DDNS
- Analog composite video output for local viewing
- Up to 50 simultaneous users

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880