

## EU2SYS-96 SERIES

### **HEATED DISPLAY SYSTEMS**



EU2SYS-96

FRONT VIEW SHOWN WITH OPTIONAL CASTERS • HALO HEAT ... a controlled, uniform heat source that gently holds and surrounds food for better appearance, taste, and longer holding life.

- Holds and displays hot food fresh and moist for hours without adding water.
- Expandable system to meet your specific requirements.

### • HOT DISPLAY CASE

ecosmart

- Curved glass styling.
- Displays hot food without condensation on glass.
- Tempered sliding glass doors reflect heat back into the products and mirror the display to enhance merchandising effect.
- Holds a full range of standard (gastronorm) pan sizes, full-size or half-size sheet pans.
- Standard stainless steel front and black painted end panels.
- Thermostatically controlled heat source radiates from the base of the display case in multiple heat zones.
- Overhead light zones with shatterproof coated bulbs.

### • DECORATOR BASE

- Designed to accommodate your choice of equipment (750-TH-II, 750-TH-II/D, 750-S, 500-2D) or optional shelf.
- Stainless steel, distinctively framed in black as standard, and brushed stainless or custom color as alternate choices.

### • SELF-SERVICE HOT DISPLAY

- Customer self-service opening is available on right side or left side of case.
- Front mounted heat-guard provides customer protection.

The display case is constructed of 18 gauge, non-magnetic stainless steel. A curved, tempered glass front encloses the display case and can be lifted to a 90 degree angle for easy cleaning. Removable, sliding glass doors on the operator side are included. Sliding door tracks have a "clean sweep" cutout allowing for easy cleaning and crumb removal. Framed end clear glass with rubber gasket material protects glass edges from chipping and breakage. The base is divided into three (3) individually managed heat zones with each zone controlled by a separate thermostat with a range of 1 through 10 and heat-on indicator light. Overhead lights are controlled by ON/OFF switches in three (3) light zones. Two (2) 125V plug outlets are available as an option on 120/208-240V units only.

П	EU2SYS-96/PL	- 96" (2438	mm) length	with BII2 base	23-3/4" (6	03mm) self-	service opening	on left side of	case front

### **FACTORY INSTALLED OPTIONS**

- The system base is not sold as a separate item. Order the full EU2SYS model to receive the base.
- Panel Color Choices
  - ⇒Specify color choice:
  - ☐ Black, standard
  - ☐ Stainless Steel, optional
  - ☐ Custom Color, optional



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.

<sup>□</sup> EU2SYS-96/PR - 96" (2438mm) length, with BU2 base, 23-3/4" (603mm) self-service opening on right side of case front




### **EU2SYS-96** SERIES

**HEATED DISPLAY SYSTEMS** 

# 

**EU2SYS Profile** 



EU2SYS-96

### INSTALLATION REQUIREMENTS

Display case must be installed level. The display case must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.

Do not install a heated display case near a cold air source such as a freezer, air conditioning vents, or in any area where outside air fluctuation can affect performance.

WEIGHT (EST.)				
MODEL	NET	SHIP		
EU2SYS-96	1366 lb (620 kg)	1425 lb (646 kg)		
EU2SYS-96/PL/PR	1374 lb (623 kg)	1434 lb (650 kg)		
CRATED DIMENSIONS:	HXWXD			
EU2SYS-96:	NOT YET AVAILABLE			

#### **DIMENSIONS** (H X W X D)

EXTERIOR, WITH BASE:

58-3/16" x 96" x 44-5/16" (1477mm x 2438mm x 1125mm)

WELL DIMENSIONS (W X L X D):

27-3/16" x 93-5/16" x 4-1/2" (690mm x 2370mm x 114mm)

ELECTRICAL					
VOLTAGE	PHASE	CYCLE/HZ	AMPS	kW	
120/208-240 (UL)	1	50/60	24.0	5.2	
at 208	1	50/60	24.0	5.2	BARE END, NO PLUG
at 240	1	50/60	24.0	5.2	
230 (CE)	1	50/60	24.3	5.6	
230	1	50/60	24.7	5.7	BARE END, NO PLUG

PAN CONFIGURATION	*	
PAN SIZE	DIMENSIONS	QTY.
FULL-SIZE & ONE-THIRD**:	12" x 20" x 2-1/2" (GN 1/1)	7
	12" x 6" x 2-1/2" (GN 1/3)	7
HALF-SIZE & ONE-THIRD**:	12" x 10" x 2-1/2" (GN 1/2)	14
	12" x 6" x 2-1/2" (GN 1/3)	7
FULL-SIZE SHEET PANS:	18" x 26" x 1"	4
MAX. CAPACITY/VOLUME:	112 lbs (51 kg)	
	70 qts (84 L)	

- \* Pans are not included with display case.
- \*\* Will also accept 4" (100mm) deep pans.

### **SPECIFICATIONS**

- Fourteen (14) overhead lights in three (3) light zones.
- Three (3) base heat zones with three (3) adjustable thermostats with a range of 1 through 10, and three (3) heat-on indicator lights.
- Four (4) tinted, reflective, tempered glass sliding doors on operator side.
- Two (2) 10" x 36" (254mm x 914mm) operator-side work shelves.
- Self-serve models EU2SYS-96/PL and EU2SYS-96/PR have a self-serve pan insert 21-5/8" x 26-7/16" x 2" (549mm x 672mm x 51mm) and includes one (1) Wire Pan Grid.

OPTIONS & ACCESSORIES			
☐ BUTTING KIT	5008523	PANEL KIT, SYSTEM	
☐ CARVING STATION	5001874	☐ BRUSHED STAINLESS STEEL	5001291
CASTERS, PLATE		□ CUSTOM COLOR	5005793
$\square$ 5" (127mm), RIGID (2 REQUIRED)	CS-2025	PLATFORM SCALE	
$\square$ 5" (127mm), SWIVEL WITH BRAKE (4 REQUIRED)	CS-2026		<b>=</b> 004 <b>2</b> 00
GAUGE, INTERIOR AMBIENT TEMP.	E00440E	☐ LEFT-HAND	5001308
☐ FULL-SERVICE CASES	5004185	☐ RIGHT-HAND	5001307
☐ SELF-SERVICE LEFT-SIDE OF CASES	5004186	SHEET PAN DIVIDER BAR PACKAGE	
□ SELF-SERVICE RIGHT-SIDE OF CASES	5004187	☐ FULL-SERVICE & SELF-SERVICE FULL CASES	5002805
☐ GLASS, TEMPERED END PANE, BRONZE KIT		☐ SELF-SERVICE LEFT-SIDE OR RIGHT-SIDE OF CASES	5002806
☐ INDEPENDENT ELECTRICAL OUTLET	5001781		3002000
☐ LOW PROFILE BASE		☐ SHELF, STAINLESS STEEL	5005786
OVERALL HEIGHT REDUCED BY 4-3/4" (121mm)	304352	☐ TEMPERATURE PROBE	5004918
PANEL KIT, COUNTER TOP  ☐ BRUSHED STAINLESS STEEL	5001283	☐ THERMOSTAT GUARD COVER PLATE	5007660
☐ CUSTOM COLOR	P153	☐ WORK SHELF WITH GRAVY LANE	5005640



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A.

PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY