Series filter head exclusively for Everpure replacement cartridges Image: The series Head: Everpare Series Head	BENEFITS
FV9272-24 Image: Statistic Statisti Statistic Statisti Statistic Statistic Statis Statisti Statiste S	BENEFITS
FV9272-24 Image: Statistic Statisti Statistic Statisti Statistic Statistic Statis Statisti Statiste S	
Mounts directly onto flat surface Change cartridges on a regular 6 month preventative maintenance program Install vertically so cartridge hangs down Change cartridges when capacity is reached or when pressure decreases Allow 2-1/2" clearance below the cartridge for casy cartridge replacement Allways flush the filter cartridge at time of installation and cartridge change	New redesigned commercial quality filter head for Everpure filter cartridges
Mounts directly onto flat surface Change cartridges on a regular 6 month preventative maintenance program Install vertically so cartridge hangs down Change cartridges when capacity is reached or when pressure decreases Allow 2-1/2" clearance below the cartridge for asy cartridge replacement Change cartridges when capacity is reached or when pressure decreases Flush filter by running water through filter Always flush the filter cartridge at time of installation and cartridge change	Series plumbed for use with a fine filter cartridg and any Everpure problem solving cartridge
Mounts directly onto flat surface Change cartridges on a regular 6 month preventative maintenance program Install vertically so cartridge hangs down Change cartridges when capacity is reached or when pressure decreases Allow 2-1/2" clearance below the cartridge for asy cartridge replacement Allways flush the filter cartridge at time of installation and cartridge change	Built-in water shut off valve and flushing valve makes cartridge change outs easy
Mounts directly onto flat surface Change cartridges on a regular 6 month preventative maintenance program Install vertically so cartridge hangs down Change cartridges when capacity is reached or when pressure decreases Allow 2-1/2" clearance below the cartridge for asy cartridge replacement Always flush the filter cartridge at time of installation and cartridge change	A cartridge nesting feature provides a more secu and durable fit
Aounts directly onto flat surface Change cartridges on a regular 6 month preventative maintenance program Install vertically so cartridge hangs down Change cartridges when capacity is reached or when pressure decreases Allow 2-1/2" clearance below the cartridge for asy cartridge replacement Always flush the filter cartridge at time of installation and cartridge change	Includes mounting box bracket and screws for fast and easy installation. No extra mounting plate is required
Aounts directly onto flat surface Change cartridges on a regular 6 month preventative maintenance program Install vertically so cartridge hangs down Change cartridges when capacity is reached or when pressure decreases Allow 2-1/2" clearance below the cartridge for asy cartridge replacement Always flush the filter cartridge at time of installation and cartridge change	New modular design of box bracket allows for future retrofitting of add-on components without disassembly of system. Optional wing bracket kits available
Aounts directly onto flat surface Change cartridges on a regular 6 month preventative maintenance program Install vertically so cartridge hangs down Change cartridges when capacity is reached or when pressure decreases Allow 2-1/2" clearance below the cartridge for asy cartridge replacement Always flush the filter cartridge at time of installation and cartridge change	All wetted parts have passed NSF extraction tes
Mounts directly onto flat surface Change cartridges on a regular 6 month preventative maintenance program Install vertically so cartridge hangs down Change cartridges when capacity is reached or when pressure decreases Allow 2-1/2" clearance below the cartridge for asy cartridge replacement Change cartridges when capacity is reached or when pressure decreases Flush filter by running water through filter Always flush the filter cartridge at time of installation and cartridge change	Engineered for durability, strength and longevity Will not corrode
Mounts directly onto flat surface Change cartridges on a regular 6 month Install vertically so cartridge hangs down Change cartridges on a regular 6 month Allow 2-1/2" clearance below the cartridge for Change cartridges when capacity is reached or Years cartridge replacement Always flush the filter cartridge at time of Flush filter by running water through filter installation and cartridge change	A P P L I C A T I O N / S I Z I N G
Install vertically so cartridge hangs downChange cartridges when capacity is reached or when pressure decreasesAllow 2-1/2" clearance below the cartridge for easy cartridge replacementChange cartridges when capacity is reached or when pressure decreasesAllow 1-1/2" clearance below the cartridge for easy cartridge replacementAllows 1-1/2Flush filter by running water through filterInstallation and cartridge change	For foodservice applications
Allow 2-1/2" clearance below the cartridge for asy cartridge replacement when pressure decreases Flush filter by running water through filter Always flush the filter cartridge at time of installation and cartridge change	Plumbed in series configuration.
Always flush the filter cartridge at time of Flush filter by running water through filter	Capacity: varies according to filter cartridge used

Twin Series Head

S P E C I F I C A T I O N S

Overall Dimensions: 6.3"H x 16.6"W x 5.5"D

Inlet connection: 3/4"

Outlet connection: 3/4"

No electrical connection required

Shipping Weight: 3 lbs.



WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



Worldwide Headquarters: EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323 - 7873 Tel (630) 307 - 3000 Fax (630) 307 - 3030 http://www.everpure.com In Europe: Pentair Water Belgium B.V./B.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals BELGIUM TEL: +32.(0).14.283.500 FAX: +32.(0).14.283.505

In Japan: Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 JAPAN TEL: 81.(0)42.775.3011 FAX: 81.(0)42.775.3015