



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLP712B

### Protect It! Surge Suppressor



#### Highlights

- 7 outlets / 12-ft. cord
- 1000 joule rating
- \$25,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's TLP712B surge suppressor offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP712B offers 7 total outlets, 12 foot cord and diagnostic LED to confirm surge suppression in present. AC suppression rated at 1000 joules shields equipment from surges and line noise. Attractive black suppressor housing with keyhole mounting slots and 1 designated transformer plug outlet offer convenient protection of desktop computer equipment and accessories. Lifetime warranty with \$25,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada Only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/12 ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/1000 joules/330V UL1449 Let-through Rating

#### Applications

- Ideal for any desktop, network or home computing application requiring AC protection

#### Package Includes

- TLP712B Surge Suppressor
- Instruction manual and warranty information

#### Features

- 1000 joules AC surge suppression shields equipment from the strongest surges and line noise
- 7 AC outlets with 1 transformer plug outlet that doesn't block remaining outlets
- 12 foot AC line cable conveniently reaches distant outlets
- Built-in power switch with integrated 15 amp circuit breaker offers power control and overload protection over all outlets
- Fail-safe thermal fusing protects against fire and other damage in the event of an extreme, extended overvoltage or surge condition
- Diagnostic LED confirms surge suppression in present
- Attractive black suppressor housing with keyhole mounting slots allow versatile placement options

- UL1449 Rated (330V all modes), UL1363 (Power Tap), cUL (Canada)
- Exceeds IEEE 587 category A & B surge suppression specifications
- Lifetime warranty with \$25,000 Ultimate Lifetime [connected equipment insurance](#) (USA, Puerto Rico & Canada Only)

## Specifications

OVERVIEW	
Intended Application	Home/Office
SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	7 NEMA 5-15R
Outlet orientation	Single row
Transformer accommodation	Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 4 transformers total
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	12 ft.
Input cord length (m)	3.7
Recommended Electrical Service	120V (110-125V)
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	1000 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20 dB
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Shipping weight (lbs)	1.8
Shipping weight (kg)	0.8
Shipping Dimensions (HWD/in)	2.2 x 5.75 x 14.9

<b>Shipping Dimensions (HWD/cm)</b>	5.6 x 14.6 x 37.8
<b>Unit weight (lbs)</b>	1
<b>Unit weight (kg)</b>	0.5
<b>Unit Dimensions (HWD/in)</b>	1.5 x 2.13 x 11.25
<b>Unit Dimensions (HWD/cm)</b>	3.8 x 5.4 x 28.6
<b>Material of construction</b>	Plastic
<b>Integrated keyhole mounting tabs</b>	Keyhole mounting slots enable wall mounting
<b>Receptacle Color</b>	Black
<b>AC line cord color</b>	Black
<b>Style</b>	Strip
<b>CERTIFICATIONS</b>	
<b>Additional International Approvals</b>	RoHS
<b>UL1449 1998 Rev. (AC Suppression)</b>	UL1449
<b>NOM (Mexico)</b>	NOM
<b>UL1363 (Power Tap)</b>	UL1363
<b>cUL / CSA (Canada)</b>	cUL
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product Warranty Period</b>	Lifetime
<b>Connected Equipment Coverage</b>	\$25,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3614](http://www.tripplite.com/en/products/model.cfm?txtModelID=3614).