

Screen 5

Three-way tri-amp system

features

- Three-way design
- THX™ approved
- Very low distortion mid-range
- Full pattern control to 300Hz
- 90° x 50° dispersion


applications

- Behind screen placement
- Premier/Showcase cinemas
- Preview theatres

The Screen 5 full-range system has been developed for use in medium to large-scale cinema environments. The system consists of a 2 x 15" (380mm) low frequency section plus a unique mid-range and high frequency horn which exhibits ideal pattern control across its operating range from 300Hz-20kHz. The Screen 5 is approved by Lucasfilm for use in category 2 (80ft or less in length and under 180000ft³ in volume) THX theatres.

The Screen 5 requires tri-amplification and would normally be operated via a THX Controller or Martin Audio DX1 Loudspeaker Management System.

overall dimensions



SCREEN_5



cinema

technical specifications

TYPE	Three-way tri-amp screen system
FREQUENCY RESPONSE (1)	45Hz-20kHz ± 3dB
DRIVERS	2 x 15" (380mm) bass driver 6.5" (165mm) mid driver 1" (25mm) exit compression driver
RATED POWER (2)	LF: 800W AES, 3200W peak MF: 150W AES, 600W peak HF: 60W AES, 240 peak
SENSITIVITY (3)	LF: 100dB MF: 107dB HF: 110dB
NOMINAL IMPEDANCE	LF: 4 ohms MF: 8 ohms HF: 8 ohms
DISPERSION (-6dB)	90° horizontal, 50° vertical
CROSSOVER	300-500Hz active, 2.2kHz active
ENCLOSURE	Vented
FINISH	Matt black
CONNECTORS	Binding Posts
DIMENSIONS	LF: (W) 670mm x (H) 1010mm x (D) 470mm (W) 26.4ins x (H) 39.8ins x (D) 18.5ins MF/HF: (W) 715mm x (H) 885mm x (D) 610mm (W) 28.1ins x (H) 34.8ins x (D) 24ins
WEIGHT	LF: 61kg (134.5lbs) MF/HF: 18kg (39.6lbs)



approved by Lucasfilm for use in THX™ theatres.

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 535312 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2003 Martin Audio Ltd.



www.martin-audio.com