



17" DRILL PRESS

The new JET model JDP-17DX - 17" Drill Press was designed especially for the woodworker. Head mounted dual AC powered laser guide system provides an accurate drilling cross point on the workpiece. The poly v-belt drive system is quiet and vibration free. This drill press also features a built-in work light to provide direct lighting on the workpiece. An extra large 14" x 18" work table provides plenty of support for larger projects.





Е

NEW

17" DRILL PRESS

FEATURES

- Innovative extra large 14" x 18" work table features: twin T-slot grooves for homemade jigs. Edge lip designed for easy clamping of work piece. Replaceable MDF center insert
- Hinged metal belt and pulley cover provides easy access to the quick
 adjustment motor mount to allow rapid spindle speed changes
- \bullet Drill press head has integrated AC work light for better work piece visibility
- · Spindle has high-quality ball bearing construction for long life
- Adjustable tension spindle return spring is ideal for repetitive drilling of the same depth
- Spindle mounted dual laser guide system provides a consistent drilling crosspoint on work piece
- Powered by a heavy-duty 3/4HP, 1Ph 115V TEFC motor and poly-v belt drive system
- Clutch-type drill stop regulates drilling depth
- Drill press is designed for left or right hand operators, handles can be placed on either side

SPECIFICATIONS

| Stock Number354173Model NumberJDP-17DXSwing (in)JDP-17DXSpindle Travel (in.)16-1/2Spindle Distance to Table (max./in.)29-1/8Spindle Distance to Base (in.)49Spindle Speed (RPM)200 - 3620Spindle Speeds16Spindle TaperMT-2Drilling Capacity (in.)5/8Chuck Size (in.)3-1/8Table Size (in.)11-1/8 x 19-5/8Base Size (in.)9Motor HP3/4HPMotor Voltage115VPrewired115VNet Weinht (lbs.)209 | | |
|--|--------------------------------------|-----------------|
| Swing (in) 16-1/2 Spindle Travel (in.) 4-3/8 Spindle Distance to Table (max./in.) 29-1/8 Spindle Distance to Base (in.) 49 Spindle Speed (RPM) 200 - 3620 Spindle Speeds 16 Spindle Taper MT-2 Drilling Capacity (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 x 18 Base Size (in.) 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Stock Number | 354173 |
| Spindle Travel (in.) 4-3/8 Spindle Distance to Table (max./in.) 29-1/8 Spindle Distance to Base (in.) 49 Spindle Speed (RPM) 200 - 3620 Spindle Speeds 16 Spindle Taper MT-2 Drilling Capacity (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 x 18 Base Size (in.) 11-1/8 x 19-5/8 Amps 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Model Number | JDP-17DX |
| Spindle Distance to Table (max./in.) 29-1/8 Spindle Distance to Base (in.) 49 Spindle Speed (RPM) 200 - 3620 Spindle Speeds 16 Spindle Taper MT-2 Drilling Capacity (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 x 18 Base Size (in.) 11-1/8 x 19-5/8 Amps 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Swing (in) | 16-1/2 |
| Spindle Distance to Base (in.) 49 Spindle Speed (RPM) 200 - 3620 Spindle Speeds 16 Spindle Taper MT-2 Drilling Capacity (in.) 5/8 Chuck Size (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 x 18 Base Size (in.) 11-1/8 x 19-5/8 Amps 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Spindle Travel (in.) | 4-3/8 |
| Spindle Speed (RPM) 200 - 3620 Spindle Speeds 16 Spindle Taper MT-2 Drilling Capacity (in.) 5/8 Chuck Size (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 × 18 Base Size (in.) 11-1/8 × 19-5/8 Amps 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Spindle Distance to Table (max./in.) | 29-1/8 |
| Spindle Speeds 16 Spindle Taper MT-2 Drilling Capacity (in.) 5/8 Chuck Size (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 x 18 Base Size (in.) 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Spindle Distance to Base (in.) | 49 |
| Spindle Taper MT-2 Drilling Capacity (in.) 5/8 Chuck Size (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 × 18 Base Size (in.) 11-1/8 × 19-5/8 Amps 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Spindle Speed (RPM) | 200 - 3620 |
| Drilling Capacity (in.) 5/8 Driums Capacity (in.) 5/8 Chuck Size (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 x 18 Base Size (in.) 11-1/8 x 19-5/8 Amps 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Spindle Speeds | 16 |
| Chuck Size (in.) 5/8 Column Diameter (in.) 3-1/8 Table Size (in.) 14 x 18 Base Size (in.) 11-1/8 x 19-5/8 Amps 9 Motor HP 3/4HP Motor Voltage 115V Prewired 115V | Spindle Taper | MT-2 |
| Column Diameter (in.) 3-1/8 Table Size (in.) 14 x 18 Base Size (in.) 11-1/8 x 19-5/8 Amps 9 Motor HP 3/4HP Motor Vhase 1Ph Motor Voltage 115V Prewired 115V | Drilling Capacity (in.) | 5/8 |
| Table Size (in.) 14 x 18 Base Size (in.) 11-1/8 x 19-5/8 Amps 9 Motor HP 3/4HP Motor Phase 1Ph Motor Voltage 115V Prewired 115V | Chuck Size (in.) | 5/8 |
| Base Size (in.) 11-1/8 x 19-5/8 Amps 9 Motor HP 3/4HP Motor Phase 1Ph Motor Voltage 115V Prewired 115V | Column Diameter (in.) | 3-1/8 |
| Amps 9 Motor HP 3/4HP Motor Phase 1Ph Motor Voltage 115V Prewired 115V | Table Size (in.) | 14 x 18 |
| Motor HP 3/4HP Motor Phase 1Ph Motor Voltage 115V Prewired 115V | Base Size (in.) | 11-1/8 x 19-5/8 |
| Motor Phase 1Ph Motor Voltage 115V Prewired 115V | Amps | 9 |
| Motor Voltage 115V Prewired 115V | Motor HP | 3/4HP |
| Prewired 115V | Motor Phase | 1Ph |
| | Motor Voltage | 115V |
| Net Weight (lbs.) 209 | Prewired | 115V |
| 100 100 gin (1200) | Net Weight (lbs.) | 209 |

OPTIONAL ACCESSORIES

| 21 pc Cobalt Drill Bit Set with Indexed Steel Case | 228237 |
|--|--------|
| 22 pc Tapered Drill Bit Set | 228244 |
| DPVC-9, 9" Drill Press Vise Clamp | 709693 |
| DPVC-11, 11" Drill Press Vise Clamp | 709692 |
| DPT-1, Drill Press Tool Tray | 709691 |





228237

228244

jettools.com

Poly-V belt drive system

Laser

Light

B. Ambidextrous handle

C. T-slot for fixture clamping

D. Replaceable insert



С

t l

Poly-V belt drive system

Laser