



Model #: CPS1500AVR

UPC: 649532015005

MSRP: \$379.99



The Smart App AVR Series CPS1500AVR UPS model has built-in Automatic Voltage Regulation (AVR) that ensures your connected equipment receives only regulated, consistent power. This model is ideal for corporate servers, departmental servers, as well as mission-critical network components.

It also features an innovative form that allows the unit to be used as either a free-standing unit, or to be rack mounted (2U). The unit also has 2 built in serial ports to allow for control of two computers during a power failure.

The battery-pack has four (4) 7AH batteries for extended runtime and is hot-swappable to minimize downtime. The CPS1500AVR guards against surges/spikes, and also offers RJ11/RJ45 dataline protection. PowerPanel Plus™ Smart Power Management software automatically saves and closes open files and shutsdowns the PC in an intelligent and orderly manner.

The CyberPower CPS1500AVR carries a 3-year warranty, coupled with our professional Technical Support and a lifetime Connected Equipment Guarantee of \$500,000.

- Automatic Voltage Regulation (AVR) - AVR technology will stabilize the AC signal and maintain a safe voltage level without switching to battery-mode. This conserves battery life, and delivers a cleaner signal to your connected equipment.
- EMI/RFI - Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- PowerPanel Plus™ Power Management Software – In the event of a power outage, PowerPanel Plus will safely save and close your open files and shut your computer down in an orderly, intelligent manner. The software allows users to view detailed information about their electrical power and the vitals of the UPS. It includes configurable system notifications, automatic self tests, adjustable high/low voltage warnings, event/data logging, and scheduled shutdowns.
- RM/T Configuration – The units can be mounted either in Tower or Rackmount (2U) form.
- Metal Housing – Rigid metal construction allows for placement in areas with a demanding environment.
- LED Indicators - LED status lights indicate Power-On and wiring faults.
- Audible Alarms - Audible tones identify when the unit is running off battery power, unit overloads, and low battery.
- Resettable Circuit Breaker - Convenient unit reset switch in case of an overload.
- 3-year Warranty - CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with product, installation, or warranty concerns --- Free of Charge!
- ISO & Safety Certifications - All CyberPower manufacturing facilities are ISO-9001 Quality Tested. Our products are also certified by the FCC, cUL, and UL.
- Windows XP Certified - PowerPanel is included Free with our UPS systems and compatible with Windows XP.



Technical Specifications

General	
Model #	CPS1500AVR
UPS Topology	Line-Interactive
Input	
Voltage	85 - 150V
Frequency	57 - 63Hz
Plug Type	NEMA 5-15P
Cord Length	10 ft
Output	
VA	1500
Watts	950
Automatic Voltage Regulation	Yes
On Battery Waveform	Simulated Sine Wave
Outlets - Total	6
Outlets - Battery & Surge	6 x NEMA 5-15R
Outlets - Surge-Only	None
Transfer Time	4 ms
Battery	
Runtime at Full-Load	6 Minutes
Runtime at Half-Load	18 Minutes
Battery Specification	4 x 12V/7Ah
Surge Protection and Filtering	
Surge Suppression	1800 Joules
Phone / Ethernet RJ11 / RJ45	1 x RJ11/45 Combo (One-in/One-out)
Coax Protection RG6	None
Management & Communications	
Indicators	LED Indicators
USB Port	None
Serial Port	2 x DB9
Software	PowerPanel Plus
SNMP / HTTP Remote Monitoring	Yes [With optional RMCARD100]
Physical	
Dimensions (WxHxD)	17.25" x 3.5" x 15.75"
Weight	57.5 lbs.
Warranty	
Product Warranty	3-year warranty. Free Tech Support.
Connected Equipment Guarantee	Lifetime
CEG Amount	\$500,000