

Fastmark 400 Series

Maximum Performance – Minimum Expense



Fastmark 400 Desktop Thermal Printers – Full-Featured, Value-Priced

For your low to moderate printing applications, the Fastmark 400 Series offers all the advantages of large-label and tag printers at a fraction of the cost. In addition, the Fastmark 400 Series uses AMT Datasouth's exclusive Printer Application Language (PAL) to provide all the benefits of a truly smart printer without re-programming your host system or requiring a dedicated PC.

Built To Last

- Tough, high-impact ABS housing
- All-metal print mechanisms
- Advanced standard features and flexible options
- Supports rich fonts, full graphics, all popular linear and 2-D barcode symbologies

Easy To Use

- No special operator training required
- Clamshell design allows full accessibility for quick media and ribbon loading
- Unique "spring loaded release" feature offers print head replacement in seconds



AMTDatasouth

PALSM
It speaks your language 

FM 400 Series – Offering Standard Features Others Consider “Add-Ons”

- Label Design Software allows printing from PC and creating stand-alone applications (not available with PAL)
- Windows™ Drivers included for 95/98/NT/2000
- Print speeds up to 3 inches per second and label lengths up to 45 inches
- 203dpi - 300dpi resolution for superior print quality, barcodes, text and graphics
- Serial and parallel interfaces
- Black Bar and Gap Sensor



PRINTER SPECIFICATIONS INCLUDE:

Models	FM402DT, FM402DT/TT, FM403DT/TT FM412DT/TT FM403 PAL, FM412 PAL
Speed	FM402DT: 2 ips (51mm/s) FM402DT/TT: 3 ips (76mm/s) FM403DT/TT: 2 ips (51mm/s) FM412DT/TT: 3 ips (76mm/s)
Print Resolution	FM402DT, FM402DT/TT: 203 dpi (8 dots/mm) FM403DT/TT: 300 dpi (12 dots/mm) FM412DT/TT: 203 dpi (8 dots/mm)
Fonts	International character sets 5 alpha-numeric fonts from .049" - 0.23"H (1.25mm-6.0mm) (not available with PAL) All fonts expandable up to 24 x 24 (not available with PAL) 4 direction 0° - 270° rotation Downloadable soft fonts (not available with PAL) Smooth scaling with PAL
Graphics & Bar Codes	Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128 (Subset A,B,C), Codabar, Interleave 2 of 5 EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A E 2&5 add on, POSTNET, German POST, Matrix 25, Maxicode, PDF-417, PCX, BMP, GDI graphics (German POST, PCX, BMP, GDI graphics - not available with PAL)
Print Width	1.0" - 4.13" (25mm - 105mm)
Print Method	FM402DT: Direct Thermal FM402DT/TT, FM403DT/TT, FM412DT/TT: Direct Thermal and Thermal Transfer
Media Size	Max width 4.3" (110mm), Min width 1.0" (25mm) Min length 0.4" (10mm) Thickness .0025" ~ .01 (.0635mm ~ .245mm) Max roll capacity 4.3" (109mm) O.D. Core size 1.0" (25mm) I.D.
Media Type	Roll, die-cut, continuous, fan-fold, tags, ticket, thermal paper, plain paper, synthetics or foils
Indexing	Black Bar and Gap

Ribbon	Thermal Transfer Models: Wax, Wax/Resin, Resin Ribbon width - 1" - 4.3" (25mm - 109mm) Ribbon roll - max O.D. 1.4" (36mm) Core size 0.5" core I.D. (12.5mm) Ribbon length - 300' (91M)
Memory/Buffer	FM402DT, FM402DT/TT: 512K standard, 512K expandable FM403DT/TT, FM412DT/TT: 2MB DRAM, 1MB FLASH
Software	Windows Drivers (95/98/NT/2000) Label creation software included (not available with PAL) PAL - FeatureMan, FlashWiz, ComLog Utilities
Emulations	Multiple Industry Emulations FM402, FM403 - A & B Industry Emulations FM412 - Z Industry Emulation FM403, FM412 - PAL Emulation
Interface	RS-232 serial, Centronics parallel, USB option
Network Interface	External LAN print server option
Physical/Electrical	W 7.3" X D 10.9" X H 6.0" (W186 X D278 X H153mm) FM402DT: 4.2 lbs. (1.9 kgs) FM402DT/TT, FM403DT/TT, FM412DT/TT: 4.6 lbs. (21. Kgs.) 110/220 VAC ± 10%, 50/60 Hz CE, UL, CUL
Environmental	40°F ~ 100°F (4°C ~ 38°C) 10 ~ 90% non condensing FCC Class B emissions
Options	Cutter Peel and Present FLASH memory card - 512K SRAM memory card - 512K Real time clock w/512K FLASH Stand alone keyboard with LCD and format storage External 8" OD Media Supply Holder RS-232 cable USB
Warranty	One year Parts and Labor, Return to Depot Six months Printhead

All products are trademarks of their respective owners. Specifications are subject to change without notice. Some models and features may not be currently available. Some options and features are not available on all models.

Part No. 110023 Rev. B

AMT Datasouth

Corporate Headquarters
4765 Calle Quetzal, Camarillo, CA 93012
(805) 388-5799 PH
(805) 484-5282 FX

Charlotte Operation
4216 Stuart Andrew Blvd., Charlotte, NC 28217
(704) 523-8500 PH
(704) 525-6104 FX

AMT Datasouth International
Unit B, Pinnacle 15, Gowerton Rd, Brackmills
Northampton, NN4 7BW, England
+44 1604 763394 PH
+44 1604 760661 FX

<http://www.amtdatasouth.com>

